

Data sheet

Product overview

The HP VPN Firewall Module Family enables advanced network protection at multigigabit speeds and combines built-in protection against denial-of-service (DoS) and hacking attacks with VPN support, zonal and virtual stateful packet inspection firewalls, application bandwidth management, IP unicast/multicast routing, and email attachment filtering. Running on the Comware OS that powers all HP enterprise switching and routing platforms also delivers a rich networking feature set that facilitates application integration and lowers an enterprise network's total cost of ownership. The modules safeguard networks from attacks and misuse while at the same time delivering policy-based, multisite connectivity for mission-critical applications such as VoIP, video, and collaboration tools. High-availability features maintain traffic flow, even in the event of network or internal device error, or loss of power to a primary device.

Key features

- Comprehensive security protection
- Industry-leading performance
- Advanced virtual firewall capabilities
- Rich VPN functionality, IPSec/GRE/L2TP
- Flexible deployment options



Features and benefits

Firewall

- Application Specific Packet Filter (ASPF): dynamically determines whether to forward or drop a packet by checking its application layer protocol information (such as FTP, HTTP, SMTP, RTSP, and other application layer protocols based on TCP/UDP) and monitoring the connection-based application layer protocol status
- Virtualization: multicore architecture enables both multiple zones and multiple separate firewall instances to be created on the same device; support for 256 security zones, 256 virtual firewalls, and 4,094 virtual LANs (VLANs) offers robust protection to all corners of your network; centralized deployment of a single device offering multiple virtual firewalls lowers total cost of ownership through streamlined training, simplified deployment and management, and reduced power consumption
- **Zone-based access policies:** logically groups virtual LANs (VLANs) into zones that share common security policies; allows both unicast and multicast policy settings by zones instead of by individual VLANs
- Application-level gateway (ALG): deep packet inspection in the firewall discovers the IP address and service port information embedded in the application data; the firewall then dynamically opens appropriate connections for specific applications
- NAT/PAT: choice of dynamic or static network address translation (NAT) preserves a network's IP address pool or conceals the private address of network resources, such as Web servers, which are made accessible to users of a guest or public wireless LAN

Virtual private network (VPN)

- **IPSec:** provides secure tunneling over an untrusted network such as the Internet or a wireless network; offers data confidentiality, authenticity, and integrity between two endpoints of the network
- Layer 2 Tunneling Protocol (L2TP): an industry standard-based traffic encapsulation mechanism supported by many common operating systems such as Windows® XP and Windows Vista®; will tunnel the Point-to-Point Protocol (PPP) traffic over the IP and non-IP networks; may use the IP/UDP transport mechanism in IP networks

- Generic Routing Encapsulation (GRE): can be used to transport Layer 2 connectivity over a Layer 3 path in a secured way; enables the segregation of traffic from site to site
- Manual or automatic Internet Key Exchange (IKE): provides both manual or automatic key exchange required for the algorithms used in encryption or authentication; auto-IKE allows automated management of the public key exchange, providing the highest levels of encryption

Management

- Secure Web GUI: provides a secure, easy-to-use graphical interface for configuring the module via HTTPS
- **Command-line interface (CLI):** provides a secure, easy-to-use command-line interface for configuring the module via SSH or a switch console; provides direct real-time session visibility
- SNMPv1, v2c, and v3: facilitate centralized discovery, monitoring, and secure management of networking devices
- Complete session logging: provides detailed information for problem identification and resolution
- Manager and operator privilege levels: enable read-only (operator) and read-write (manager) access on CLI and Web browser management interfaces
- **Remote monitoring (RMON):** uses standard SNMP to monitor essential network functions; supports events, alarm, history, and statistics group plus a private alarm extension group
- FTP, TFTP, and SFTP support: FTP allows bidirectional transfers over a TCP/IP network and is used for configuration updates; Trivial FTP is a simpler method using User Datagram Protocol (UDP)

Layer 3 routing

- Static IP routing: provides manually configured routing; includes ECMP capability
- Routing Information Protocol (RIP): provides RIPv1 and RIPv2 routing
- **OSPF:** includes host-based ECMP to provide link redundancy/scalable bandwidth and NSSA
- Border Gateway Protocol 4 (BGP-4): Exterior Gateway Protocol (EGP) with path vector protocol uses TCP for enhanced reliability for the route discovery process, reduces bandwidth consumption by advertising only incremental updates, and supports extensive policies for increased flexibility, as well as scales to very large networks

- **Dual IP stack:** maintains separate stacks for IPv4 and IPv6 to ease transition from an IPv4-only network to an IPv6-only network design
- **Policy routing:** allows custom filters for increased performance and security; supports ACLs, IP prefix, AS paths, community lists, and aggregate policies
- Layer 3 IPv6 routing: provides routing of IPv6 at media speed; supports static routes, RIPng, OSPFv3, IS-ISv6, and MP-BGP

Security

- **Defense against attacks:** A-Series firewalls provide defenses against various attacks, such as DoS/DDoS, ARP spoofing, large ICMP packets, address/port scanning, Tracert, IP packets with the Record Route option, and static and dynamic blacklists; also support binding of MAC address and IP address, as well as intelligent defense against worms and viruses
- Application layer content filtering: A-Series firewalls support mail filtering, based on SMTP mail address, titles, attachments, and content; support Web page filtering, including HTTP URL and content filtering
- Multiple security authentication services: A-Series firewalls support RADIUS and HWTACACS authentication, certificate-based (x.509 format) PKI/CA authentication, and user entitlement
- Centralized management and auditing: A-Series firewalls provide logging, traffic statistics and analysis, event monitoring and statistics, and mail notification and alarms

Warranty and support

- **1-year warranty:** with advance replacement and 10-calendar-day delivery (available in most countries)
- Electronic and telephone support: limited electronic and telephone support is available from HP; to reach our support centers, refer to www.hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, refer to www.hp.com/networking/warrantysummary
- **Software releases:** to find software for your product, refer to <u>www.hp.com/networking/support</u>; for details on the software releases available with your product purchase, refer to <u>www.hp.com/networking/warrantysummary</u>

Specifications

	HP 9500 VPN Firewall Module (JD245A)	HP 7500 Advanced VPN Firewall Module (JD249A)
Ports	2 RJ-45 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)	2 RJ-45 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)
	2 dual-personality ports; auto-sensing 10/100/1000BASE-T or SFP	2 dual-personality ports; auto-sensing 10/100/1000BASE-T or SFP
	1 RJ-45 serial console port	1 RJ-45 serial console port
	1 Compact Flash port	1 Compact Flash port
Physical characteristics		
Dimensions Weight	14.92(d) x 15.71(w) x 1.58(h) in. (37.9 x 39.9 x 4.01 cm) 7.72 lb. (3.5 kg)	14.84(d) x 15.71(w) x 1.57(h) in. (37.7 x 39.9 x 4 cm) 7.72 lb. (3.5 kg)
Environment	7.7 2 ID. (0.0 NG)	7.7 Z ID. (0.5 Kg)
Operating temperature	32°F to 113°F (0°C to 45°C)	32°F to 113°F (0°C to 45°C)
Operating relative humidity	10% to 95%, noncondensing	10% to 95%, noncondensing
Management	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; HTTPS; RMON1; FTP	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; HTTPS; RMON1; FTP
Features	Performance	Performance
	- 8 Gbps firewall throughput	- 6.5 Gbps firewall throughput
	- 2 million concurrent connections	- 2 million concurrent connections
	- 60,000 new connections per second	- 60,000 new connections per second
	- Maximum 20,480 security policies	- Maximum 20,480 security policies
	- 2 Gbps 3DES/AES VPN throughput	- 2 Gbps 3DES/AES VPN throughput
	- 5,000 IPSec tunnels	- 5,000 IPSec tunnels
	- 4,000 VLANs	- 4,000 VLANs
	Firewall operation mode	Firewall operation mode
	- Routing mode	- Routing mode
	- Transparent mode	- Transparent mode
	- Hybrid mode	- Hybrid mode
	AAA service	AAA service
	- Local authentication	- Local authentication
	- Standard RADIUS	- Standard RADIUS
	- HWTACACS+	- HWTACACS+
	- RADIUS domain authentication	- RADIUS domain authentication
	ASPF	ASPF
	- General TCP/UDP application	- General TCP/UDP application
	- FTP/SMTP/HTTP/RTSP/H323 Protocol State Detection	- FTP/SMTP/HTTP/RTSP/H323 Protocol State Detection
	- SIP/MGCP/QQ/MSN Protocol State Detection	- SIP/MGCP/QQ/MSN Protocol State Detection
	- Java/ActiveX blocking and detection	- Java/ActiveX blocking and detection
	- Port mapping	- Port mapping
	- Support for the fragmented packets	- Support for the fragmented packets
	Virtualization	Virtualization
	- 256 virtual firewalls	- 256 virtual firewalls
	- 4 default security zones	- 4 default security zones
	- Maximum 256 security zones	- Maximum 256 security zones
	NAT	NAT
	- NAPT	- NAPT
	- PAT	- PAT
	- NAT server	- NAT server
	- Port mapping	- Port mapping Ridicational NAT
	- Bidirectional NAT	- Bidirectional NAT
	- Static NAT Network security	- Static NAT Network security
	- Add blacklist by hand or automatically	- Add blacklist by hand or automatically
	- Add blacklist by hand or automatically - IP+MAC binding	- Add blacklist by hand of dutomatically - IP+MAC binding
	- IF+MAC binding - ARP Reverse Query	- ARP Reverse Query
	- ARP Cheat Check	- ARP Cheat Check
	- Management ports closed by default	- Management ports closed by default
	- Management ports closed by default	DDOS
	- DNS Query flood	- DNS Query flood
	- SYN flood	- SYN flood
	- Autostarts TCP Proxy when detects SYN flood	- Autostarts TCP Proxy when detects SYN flood
	- Autostatis TCr Froxy when delects 311N 1100a	- Autosians ICF Froxy when delecis 3111 11000

HP 9500 VPN Firewall Module (JD245A)	HP 7500 Advanced VPN Firewall Module (JD249A)
- ICMP flood	- ICMP flood
- UDP flood	- UDP flood
- IP spoofing	- IP spoofing
- SQL injection filter	- SQL injection filter
L2TP VPN	L2TP VPN
- LNS, LAC	- LNS, LAC
- L2TP Multi-instance	- L2TP Multi-instance
GRE	GRE
- GRE tunneling protocol	- GRE tunneling protocol
IPSec	IPSec
- AH/ESP	- AH/ESP
- ESP	- ESP
- Transport/tunnel	- Transport/tunnel
- NAT traversal	- NAT traversal
- Strategy template	- Strategy template
IKE	IKE
- DH	- DH
- Preshare key authentication method	- Preshare key authentication method
 Support aggressive mode and main exchange mode 	 Support aggressive mode and main exchange mode
- IKE DPD, PKI/CA	- IKE DPD, PKI/CA
Network feature	Network feature
- IEEE 802.1q VLAN	- IEEE 802.1q VLAN
- 4,000 subinterfaces	- 4,000 subinterfaces
- Static and dynamic ARP	- Static and dynamic ARP
- Multicast, PIM	- Multicast, PIM
- IGMPv1/v2/v3	- IGMPv1/v2/v3
Routing	Routing
- RIP	- RIP
- OSPF	- OSPF
- BGP	- BGP
- Static route	- Static route
- Policy route	- Policy route
High availability	High availability
- Active-active mode	- Active-active mode
 Active-passive mode Session synchronization for firewall 	 Active-passive mode Session synchronization for firewall
System management	System management
- Web management support for Internet Explorer/Firefox	- Web management support for Internet Explorer/Firefox
- Command-line interface (Console/Telnet/SSH)	- Command-line interface (Console/Telnet/SSH)
- Classification Manager	- Classification Manager
- Unified management through iMC	- Unified management through iMC
- SNMPv2c/v3	- SNMPv1/v2c/v3
Administration	Administration
- Software upgrades	- Software upgrades
- Configuration backup and restore	- Configuration backup and restore
Logging/Monitoring	Logging/Monitoring
- Syslog	- Syslog
- Mini RMON	- Mini RMON
- NTP	- NTP
- NAT/ASPF/firewall log stream (Binary log)	- NAT/ASPF/firewall log stream (Binary log)
IPv6 routing and multicast	IPv6 routing and multicast
- RIPng	- RIPng
- OSPFv3	- OSPFv3
- BGP4+	- BGP4+
- Static route	- Static route
- Policy route	- Policy route
- PIM-SM/DM	- PIM-SM/DM
IPv6 security	IPv6 security
- NAT-PT	- NAT-PT
- Manual tunnel	- Manual tunnel

	HP 9500 VPN Firewall Module (JD245A)	- IPvó over IPv4 GRE tunnel	
	- IPv6 over IPv4 GRE tunnel		
	- 6to4 tunnel (RFC 3056)	- 6to4 tunnel (RFC 3056)	
	- ISATAP tunnel	- ISATAP tunnel	
	- IPv6 packet filter	- IPv6 packet filter	
	- RADIUS	- RADIUS	
	- NAT64	- NAT64	
ervices	3-year, parts only, global next-day advance exchange (UZ896E)	3-year, parts only, global next-day advance exchange (UZ896E)	
	3-year, 4-hour onsite, 13x5 coverage for hardware (UZ897E)	3-year, 4-hour onsite, 13x5 coverage for hardware (UZ897E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware (UZ900E)	3-year, 4-hour onsite, 24x7 coverage for hardware (UZ900E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UZ904E)	3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UZ904E)	
	3-year, 24x7 SW phone support, software updates (UZ907E)	3-year, 24x7 SW phone support, software updates (UZ907E)	
	1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR735E)	1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR735E)	
	1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR736E)	1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR736E)	
	1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR737E)	1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR737E)	
	4-year, 4-hour onsite, 13x5 coverage for hardware (UZ898E)	4-year, 4-hour onsite, 13x5 coverage for hardware (UZ898E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware (UZ901E)	4-year, 4-hour onsite, 24x7 coverage for hardware (UZ901E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UZ941E)	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UZ905E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UZ905E)	4-year, 24x7 SW phone support, software updates (UZ908E)	
	4-year, 24x7 SW phone support, software updates (UZ908E)	5-year, 4-hour onsite, 13x5 coverage for hardware (UZ899E)	
	5-year, 4-hour onsite, 13x5 coverage for hardware (UZ899E)	5-year, 4-hour onsite, 24x7 coverage for hardware (UZ902E)	
	5-year, 4-hour onsite, 24x7 coverage for hardware (UZ902E)	5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UZ906E)	
	5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UZ906E)	5-year, 24x7 SW phone support, software updates (UZ909E)	
	5-year, 24x7 SW phone support, software updates (UZ909E)	3 Yr 6 hr Call-to-Repair Onsite (UZ910E)	
	3 Yr 6 hr Call-to-Repair Onsite (UZ910E)	4 Yr 6 hr Call-to-Repair Onsite (UZ911E)	
	4 Yr 6 hr Call to Repair Onsite (UZ911E)	5 Yr 6 hr Call-to-Repair Onsite (UZ912E)	
	5 Yr 6 hr Call-to-Repair Onsite (UZ912E)	1-year, 6 hour Call-To-Repair Onsite for hardware (HR739E)	
	1-year, 6 hour Call-To-Repair Onsite for hardware (HR739E)	1-year, 24x7 software phone support, software updates (HR738E)	
	1-year, 24x7 software phone support, software updates (HR738E)	Refer to the HP website at <u>www.hp.com/networking/services</u> for details on th service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	
	Refer to the HP website at <u>www.hp.com/networking/services</u> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.		

Specifications (continued)

Standards and protocols

IPv6 RFC 1981 IPv6 Path MTU Discovery

RFC 2460 IPv6 Specification

RFC 2465 Management Information Base for IP Version 6: Textual Conventions and General

Group(partially support, only "IPv6 Interface

Statistics table") RFC 3484 Default Address Selection for IPv6

RFC 3513 IPv6 Addressing Architecture

RFC 3587 IPv6 Global Unicast Address Format

RFC 4007 IPv6 Scoped Address Architecture

- RFC 4862 IPv6 Stateless Address Auto-configuration
- Security RFC 1321 The MD5 Message-Digest Algorithm RFC 1334 PPP Authentication Protocols (PAP) RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP) RFC 2104 Keyed-Hashing for Message Authentication RFC 2138 RADIUS Authentication RFC 2618 RADIUS Authentication Client MIB RFC 2620 RADIUS Accounting Client MIB RFC 2716 PPP EAP TLS Authentication Protocol RFC 2865 RADIUS (client only) RFC 2865 RADIUS Authentication RFC 2867 RADIUS Accounting Modifications for Tunnel Protocol Support RFC 2868 RADIUS Attributes for Tunnel Protocol Support RFC 2869 RADIUS Extensions draft-grant-tacacs-02 (TACACS)

VPN

RFC 1701 Generic Routing Encapsulation (GRE)

HP 7500 Advanced VPN Firewall Module (JD249A)

IKEv1

RFC 1702 Generic Routing Encapsulation over IPv4 networks RFC 1828 IP Authentication using Keyed MD5

RFC 1829 The ESP DES-CBC Transform RFC 1853 IP in IP Tunneling

RFC 2085 HMAC-MD5 IP Authentication with

Replay Prevention

RFC 2401 Security Architecture for the Internet Protocol

RFC 2402 IP Authentication Header

RFC 2403 - HMAC-MD5-96 RFC 2403 The Use of HMAC-MD5-96 within ESP

and AH RFC 2404 The Use of HMAC-SHA-1-96 within ESP

and AH RFC 2405 The ESP DES-CBC Cipher Algorithm With

Explicit IV RFC 2406 IP Encapsulating Security Payload (ESP) RFC 2410 The NULL Encryption Algorithm and Its

Use With IPsec RFC 2411 IP Security Document Roadmap

RFC 2451 The ESP CBC-Mode Cipher Algorithms

RFC 2473 Generic Packet Tunneling in IPv6

Specification RFC 2529 Transmission of IPv6 over IPv4 Domains without Explicit Tunnels

RFC 2661 Layer Two Tunneling Protocol "L2TP" RFC 2784 Generic Routing Encapsulation (GRE) RFC 2868 RADIUS Attributes for Tunnel Protocol

Support

RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers

RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec

RFC 4214 Intra-Site Automatic Tunnel Addressing Protocol (ISATAP)

RFC 2407 The Internet IP Security Domain of Interpretation for ISAKMP RFC 2408 Internet Security Association and Key Management Protocol (ISAKMP). RFC 2409 The Internet Key Exchange (IKE) RFC 2412 The OAKLEY Key Determination Protocol RFC 3526 More Modular Exponential (MODP) Diffie-Hellman groups for Internet Key Exchange (IKE) RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers

PKI

RFC 2511 Internet X.509 Certificate Request Message Format RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile draft-nourse-scep-06: PKCS#1 PKCS#10

PKCS#12 PKCS#7

	HP 8800 Firewall Processing Module (JD251A)	HP 12500 VPN Firewall Module (JC635A)
Ports	2 RJ-45 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)	2 RJ-45 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)
	2 dual-personality ports; auto-sensing 10/100/1000BASE-T or SFP	2 RJ-45 dual-personality ports; auto-sensing 10/100/1000BASE-T or SFP
	1 RJ-45 serial console port	1 RJ-45 serial console port
	1 Compact Flash port	1 Compact Flash port
Physical characteristics		
Dimensions	14.92(d) x 15.71(w) x 1.57(h) in. (37.9 x 39.9 x 4.0 cm)	19.65(d) x 15.71(w) x 1.57(h) in. (49.9 x 39.9 x 4 cm)
Weight	7.72 lb. (3.5 kg)	7.72 lb. (3.5 kg)
Environment		
Operating temperature	32°F to 113°F (0°C to 45°C)	32°F to 113°F (0°C to 45°C)
Operating relative humidity	10% to 95%, noncondensing	10% to 95%, noncondensing
Management	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; HTTPS; RMON1; FTP	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; HTTPS; RMON1; FTP
Features	Performance	Performance
	- 8 Gbps firewall throughput	- 10 Gbps firewall throughput
	- 2 million concurrent connections	- 2 million concurrent connections
	- 60,000 new connections per second	- 60,000 new connections per second
	- Maximum 20,480 security policies	- Maximum 20,480 security policies
	- 2 Gbps 3DES/AES VPN throughput	- 2 Gbps 3DES/AES VPN throughput
	- 5,000 IPSec tunnels	- 5,000 IPSec tunnels
	- 4,000 VLANs	- 4,000 VLANs
	Firewall operation mode	Firewall operation mode
	- Routing mode	- Routing mode
	- Transparent mode	- Transparent mode
	- Hybrid mode	- Hybrid mode
	AAA service	AAA service
	- Local authentication	- Local authentication
	- Standard RADIUS	- Standard RADIUS
	- HWTACACS+	- HWTACACS+
	- RADIUS domain authentication ASPF	- RADIUS domain authentication ASPF
	 General TCP/UDP application FTP/SMTP/HTTP/RTSP/H323 Protocol State Detection 	- General TCP/UDP application
	- SIP/MGCP/QQ/MSN Protocol State Detection	- FTP/SMTP/HTTP/RTSP/H323 Protocol State Detection - SIP/MGCP/QQ/MSN Protocol State Detection
	- Java/ActiveX blocking and detection	- Java/ActiveX blocking and detection
	- Port mapping	- Port mapping
	- Support for the fragmented packets	- Support for the fragmented packets
	Virtualization	Virtualization
	- 256 virtual firewalls	- 256 virtual firewalls
	- 4 default security zones	- 4 default security zones
	- Maximum 256 security zones	- Maximum 256 security zones
	NAT	NAT
	- NAPT	- NAPT
	- PAT	- PAT
	- NAT server	- NAT server
	- Port mapping	- Port mapping
	- Bidirectional NAT	- Bidirectional NAT
	- Static NAT	- Static NAT
	Network security	Network security
	- Add blacklist by hand or automatically	- Add blacklist by hand or automatically
	- IP+MAC binding	- IP+MAC binding
	- ARP Reverse Query	- ARP Reverse Query
	- ARP Cheat Check	- ARP Cheat Check
	- Management ports closed by default	- Management ports closed by default
	DDOS	DDOS
	- DNS Query flood	- DNS Query flood
	- SYN flood	- SYN flood
	- Autostarts TCP Proxy when detects SYN flood	- Autostarts TCP Proxy when detects SYN flood

- Manual tunnel

Specifications (continued)

HP 8800 Firewall Processing Module (JD251A) HP 12500 VPN Firewall Module (JC635A) - ICMP flood - ICMP flood - UDP flood - UDP flood - IP spoofing - IP spoofing - SQL injection filter - SQL injection filter L2TP VPN L2TP VPN -INS IAC - LNS, LAC - L2TP Multi-instance - L2TP Multi-instance GRE GRE - GRE tunneling protocol - GRE tunneling protocol IPSec IPSec - AH/ESP - AH/ESP - ESP - ESP - Transport/tunnel - Transport/tunnel - NAT traversal - NAT traversal - Strategy template - Strategy template IKE IKE - DH - DH - Preshare key authentication method - Preshare key authentication method - Support aggressive mode and main exchange mode - Support aggressive mode and main exchange mode - IKE DPD, PKI/CA - IKE DPD, PKI/CA Network feature Network feature - IEEE 802.1q VLAN - IEEE 802.1q VLAN - 4,000 subinterfaces - 4,000 subinterfaces - Static and dynamic ARP - Static and dynamic ARP - Multicast, PIM - Multicast, PIM - IGMPv1/v2/v3 - IGMPv1/v2/v3 Routing Routing - RIP - RIP - OSPF - OSPF - BGP - BGP - Static route - Static route - Policy route - Policy route High availability High availability - Active-active mode - Active-active mode - Active-passive mode - Active-passive mode - Session synchronization for firewall - Session synchronization for firewall System management System management - Web management support for Internet Explorer/Firefox - Web management support for Internet Explorer/Firefox - Command-line interface (Console/Telnet/SSH) - Command-line interface (Console/Telnet/SSH) - Classification Manager - Classification Manager - Unified management through iMC - Unified management through iMC - SNMPv2c/v3 - SNMPv1/v2c/v3 Administration Administration - Software upgrades - Software upgrades - Configuration backup and restore - Configuration backup and restore Logging/Monitoring Logging/Monitoring - Syslog - Syslog - Mini RMON - Mini RMON - NTP - NTP - NAT/ASPF/firewall log stream (Binary log) - NAT/ASPF/firewall log stream (Binary log) IPv6 routing and multicast IPv6 routing and multicast - RIPng - RIPng - OSPFv3 - OSPFv3 - BGP4+ - BGP4+ - Static route - Static route - Policy route - Policy route - PIM-SM/DM - PIM-SM/DM IPv6 security IPv6 security - NAT-PT - NAT-PT

- Manual tunnel

	HP 8800 Firewall Processing Module (JD251A)	HP 12500 VPN Firewall Module (JC635A)	
	- IPv6 over IPv4 GRE tunnel	- IPv6 over IPv4 GRE tunnel	
	- 6to4 tunnel (RFC 3056)	- 6to4 tunnel (RFC 3056)	
	- ISATAP tunnel	- ISATAP tunnel	
	- IPv6 packet filter	- IPv6 packet filter	
	- RADIUS	- RADIUS	
	- NAT64	- NAT64	
iervices	3-year, parts only, global next-day advance exchange (UZ968E)	Refer to the HP website at <u>www.hp.com/networking/services</u> for details on th service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	
	3-year, 4-hour onsite, 13x5 coverage for hardware (UZ969E)		
	3-year, 4-hour onsite, 24x7 coverage for hardware (UZ972E)		
	3-year, 4-hour onsite, 24x7 coverage for hardware (HR756E)		
	3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UZ976E)		
	3-year, 24x7 SW phone support, software updates (UZ979E)		
	1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR755E)		
	1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR757E)		
	4-year, 4-hour onsite, 13x5 coverage for hardware (UZ970E)		
	4-year, 4-hour onsite, 24x7 coverage for hardware (UZ973E)		
	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UZ977E)		
	4-year, 24x7 SW phone support, software updates (UZ980E)		
	5-year, 4-hour onsite, 13x5 coverage for hardware (UZ971E)		
	5-year, 4-hour onsite, 24x7 coverage for hardware (UZ974E)		
	5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UZ978E)		
	5-year, 24x7 SW phone support, software updates (UZ981E)		
	3 Yr 6 hr Call-to-Repair Onsite (UZ982E)		
	4 Yr 6 hr Call-to-Repair Onsite (UZ983E)		
	5 Yr 6 hr Call-to-Repair Onsite (UZ984E)		
	1-year, 6 hour Call-To-Repair Onsite for hardware (HR759E)		
	1-year, 24x7 software phone support, software updates (HR758E)		
	Refer to the HP website at <u>www.hp.com/networking/services</u> for details on the service-level descriptions and product numbers. For details about services and		
	response times in your area, please contact your local HP sales office.		

Specifications (continued)

	ΗP	8800	Firewall	Processing	Module	(JD251A)
--	----	------	----------	------------	--------	----------

Standards	and	protocols
-----------	-----	-----------

IPv6

ŀ

RFC 1981 IPv6 Path MTU Discovery

RFC 2460 IPv6 Specification RFC 2465 Management Information Base for IP

Version 6: Textual Conventions and General Group(partially support, only "IPv6 Interface

Statistics table") RFC 3484 Default Address Selection for IPv6

- RFC 3513 IPv6 Addressing Architecture
- RFC 3587 IPv6 Global Unicast Address Format
- RFC 4007 IPv6 Scoped Address Architecture
- RFC 4862 IPv6 Stateless Address Auto-configuration

Security RFC 1321 The MD5 Message-Digest Algorithm RFC 1334 PPP Authentication Protocols (PAP) RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP) RFC 2104 Keyed-Hashing for Message Authentication RFC 2138 RADIUS Authentication RFC 2618 RADIUS Authentication Client MIB RFC 2620 RADIUS Accounting Client MIB RFC 2716 PPP EAP TLS Authentication Protocol RFC 2865 RADIUS (client only) RFC 2865 RADIUS Authentication RFC 2867 RADIUS Accounting Modifications for Tunnel Protocol Support RFC 2868 RADIUS Attributes for Tunnel Protocol Support RFC 2869 RADIUS Extensions

draft-grant-tacacs-02 (TACACS)

VPN

RFC 1701 Generic Routing Encapsulation (GRE)

HP 12500 VPN Firewall Module (JC635A)

RFC 1702 Generic Routing Encapsulation over IPv4 networks

RFC 1828 IP Authentication using Keyed MD5 RFC 1829 The ESP DES-CBC Transform

RFC 1853 IP in IP Tunneling

RFC 2085 HMAC-MD5 IP Authentication with Replay Prevention

RFC 2401 Security Architecture for the Internet Protocol

RFC 2402 IP Authentication Header

RFC 2403 - HMAC-MD5-96 RFC 2403 The Use of HMAC-MD5-96 within ESP

and AH RFC 2404 The Use of HMAC-SHA-1-96 within ESP

and AH RFC 2405 The ESP DES-CBC Cipher Algorithm With

Explicit IV RFC 2406 IP Encapsulating Security Payload (ESP)

RFC 2410 The NULL Encryption Algorithm and Its Use With IPsec

RFC 2411 IP Security Document Roadmap RFC 2451 The ESP CBC-Mode Cipher Algorithms

RFC 2473 Generic Packet Tunneling in IPv6

Specification

RFC 2529 Transmission of IPv6 over IPv4 Domains without Explicit Tunnels

RFC 2661 Layer Two Tunneling Protocol "L2TP" RFC 2784 Generic Routing Encapsulation (GRE) RFC 2868 RADIUS Attributes for Tunnel Protocol

Support

RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers

RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec

RFC 4214 Intra-Site Automatic Tunnel Addressing Protocol (ISATAP)

IKEv1 RFC 2407 The Internet IP Security Domain of Interpretation for ISAKMP RFC 2408 Internet Security Association and Key Management Protocol (ISAKMP). RFC 2409 The Internet Key Exchange (IKE) RFC 2412 The OAKLEY Key Determination Protocol RFC 3526 More Modular Exponential (MODP) Diffie-Hellman groups for Internet Key Exchange (IKE) RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers

PKI

RFC 2511 Internet X.509 Certificate Request Message Format RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile draft-nourse-scep-06:

PKCS#1 PKCS#10 PKCS#12 PKCS#7

HP VPN Firewall Module Family accessories

Memory

HP X600 1G Compact Flash Card (JC684A) HP X600 512M Compact Flash Card (JC685A) HP X600 256M Compact Flash Card (JC686A)

To learn more, visit www.hp.com/networking

© Copyright 2011-2012 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Windows and Windows Vista are U.S. registered trademarks of Microsoft Corporation. Java is a registered trademark of Oracle and/or its affiliates.

4AA3-7162ENW, Created September 2011; Updated March 2012, Rev. 1

